







SPECIFICATIONS LV800 PRO	
Engine	Kohler Common Rail Turbo Intercooler 55 Kw
Horsepower	75.5HP
Torque	300 Nm
Fuel type	Diesel
Fuel capacity (L)	52
Ground speed (Km/hr)	9
Standard Flail Weight	300-500kg
Machine Weight only	1700kg
Flail Speed	3300 rpm
Machine Height	1190mm
Machine Length	2430mm
Machine Width	1510-1910mm
Main attachment pump	(piston closed loop) 106 lt/min @ 350bar
Service pump	27.5 lt/min @ 180bar
Extendable undercarriage	(Closed) 1510 mm - (Open) 1910 mm
Attachment sideshifting	(Hydraulic) 500 mm + (Mechanical) 584 mm
	Dellat Faulta Churan Crindan
Attachments	Pallet Forks Stump Grinder
	Loader Bucket Grapple
	Standard Y Flail Sprayer
	Heavy Duty Forestry Flail

FEATURES	
Powerful 4-cylinder KOHLER TURBO INTERCOOLER COMMON RAIL ENGINE	Patented undercarriage to climb steep slopes and anti-de-tracking system of the tracks.
Engine lubrication patented by MDB for continuous use on steep slopes of up to $60^{\circ}$ .	The reversible fan and an oversized radiator allow for continuous work at full power also at high outside temperatures.
The integrated hydraulic side-shifting plate allows for lateral adjustment of the attachment of up to 500mm.	The totally hydraulic floating attachment plate of mulcher allows the tool to remain constantly in contact with the floor.
Integrated cylinders allow for widening of the tracks from 1510mm up to 1910mm (patented system).	3 fully-proportional auxiliary lines. Winch integrated into the frame.
Main attachment pump with proportional flow control.	Quick exchange plate: With a single "click" all hydraulic connections are made. Tow hook.

www.greenclimber.com.au

- (f) greenclimberaustralia
- greenclimberau