

**Green Climber**  
Challenge Accepted!



LV800

# LV800



## REMOTE CONTROLLED SLOPE MOWER

### SPECIFICATIONS LV800

Engine	Kohler Common Rail Turbo Intercooler 55 Kw	
Horsepower	75HP	
Torque	300 Nm	
Fuel type	Diesel	
Fuel capacity (L)	52	
Ground speed (Km/hr)	9	
Standard Flail Weight	300-500kg	
Machine Weight only	1700kg	
Flail Speed	3300 rpm	
Machine Height	1190mm	
Machine Length	2430mm	
Machine Width	1250mm	
Track Width	1510-1910mm	
Main attachment pump	(piston closed loop) 106 lt/min @ 350bar	
Service pump	27.5 lt/min @ 180bar	
Extendable undercarriage	(Closed) 1510 mm - (Open) 1910 mm	
Attachment sideshifting	(Hydraulic) 500 mm + (Mechanical) 584 mm	
Attachments	Forklift	Stump Grinder
	Bucket	Flail
	Heavy Duty Forestry Flail	

### FEATURES

Powerful 4-cylinder KOHLER TURBO INTERCOOLER COMMON RAIL ENGINE	Patented undercarriage to climb steep slopes and anti-de-tracking system of the tracks.
Engine lubrication patented by MDB for continuous use on steep slopes of up to 60°.	The reversible fan and an oversized radiator allow for continuous work at full power also at high outside temperatures.
The integrated hydraulic side-shifting plate allows for lateral adjustment of the attachment of up to 500mm.	The totally hydraulic floating attachment plate of mulcher allows the tool to remain constantly in contact with the floor.
Integrated cylinders allow for widening of the tracks from 1510mm up to 1910mm (patented system).	3 fully-proportional auxiliary lines. Winch integrated into the frame.
Main attachment pump with proportional flow control.	Quick exchange plate: With a single "click" all hydraulic connections are made. Tow hook.

[www.greenclimber.com.au](http://www.greenclimber.com.au)

greenclimberaustralia

greenclimberau

©Copyright 2021. All rights reserved. Prices and Specifications subject to change without notice.